

ANTIFREEZER G12 55%

Pink antifreezer refrigerant

Antifreezer & Coolant for direct use, made from glycols and corrosion inhibitors of high technology to provide complete protection to all components of the refrigeration circuit. Excellent corrosion protection for all metals and alloys in the circuit, as well as high cooling and boiling power. Concentration: 55%. Freezing point: -37.5 ° C. Boiling point: + 140 ° C. Suitable for any type of vehicle.

MODE OF USE

Direct use. Do not dilute. Comply with UNE 26-361-88, ASTM D 3306; ASTM D 4985, VW TL 774D.

CHARACTERISTICS

Appearance: Transparent
Color: Pink
Odor: Odourless
pH: 7,5 - 8,5

Chemical description: Glycol/s

Skin Sens. 1: H317 - May cause an allergic skin reaction.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P501 Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Substances that contribute to the classification: Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239-6] (3:1)

Maximum V.O.C. content: 213,79 g/L (20 °C)

Warning

