

# ANTIFREEZER 30%

## Green antifreezer refrigerant

Antifreezer & Coolant for direct use, made from glycols and corrosion inhibitors of high technology to provide complete protection to all components of the refrigeration circuit. Excellent corrosion protection for all metals and alloys in the circuit, as well as high cooling and boiling power. Concentration: 30%; Freezing point: -18°C; Boiling point: 117 ° C. Applicable to any car brand. It protects metal parts of the circuit. Anticorrosive and descaling.

### MODE OF USE

Direct use, do not dilute.

### CHARACTERISTICS

Appearance: Transparent  
Color: Green  
Odor: Characteristic  
pH: 7,5 - 8,5

**Chemical description:** Glycol/s

Skin Sens. 1: H317 - May cause an allergic skin reaction. Acute Tox. 4: H302 - Harmful if swallowed.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P330 Rinse mouth. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P501 Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Substances that contribute to the classification: Ethanediol; Sodium nitrite; Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)

Maximum V.O.C. content: 309,64 g/L (20 °C)

### Warning

